

Model 6-23、6-30 Centrifugal Blower

Model 6-23、6-30 Centrifugal Blower is generally used in the conveying of grain or powder, as well as widely used in the conveying of air or other gas which may not self-ignite, do not contain glutinous matter. The medium temperature is no more than 50°C (no more than 80°C of the highest temperature). The dust or grain matter contained in the medium is no more than 150mg/m³. Centrifugal Blower is generally used in the conveying of grain or powder, as well as widely used in the conveying of air or other gas which may not self-ignite, do not contain glutinous matter. The medium temperature is no more than 50°C (no more than 80°C of the highest temperature). The dust or grain matter contained in the medium is no more than 150mg/m³.

Shuangcheng Blower

Model 6-23 Centrifugal Blower Datasheet

No.	Type	r/min	No.	Total pressure Pa	Flux m ³ /h	Power kW	motor	
							Type	Power kW
4	A	2840	1	2617	682	0.84	Y90L-2	2.2
			2	2542	802	0.86		
			3	2529	921	0.94		
			4	2328	1015	1.01		
			5	2196	1108	1.06		
			6	2065	1202	1.11		
			7	1863	1296	1.15		
5	A	2880	1	4090	1332	2.56	Y112M-2	4
			2	3972	1566	2.63		
			3	3952	1799	2.87		
			4	3638	1982	3.06		
			5	3432	2165	3.23		
			6	3226	2348	3.38		
			7	2911	2532	3.52		
5	C	2500	1	3082	1156	1.67	Y100L-2	3
			2	2993	1359	1.72		
			3	2978	1561	1.88		
			4	2741	1720	2.00		
			5	2586	1879	2.11		
			6	2461	2038	2.21		
			7	2193	2198	2.30		
6	A	2900	1	5884	2301	6.23	Y160M-2	11
			2	5717	2706	6.94		
			3	5688	3108	7.72		
			4	5237	3424	7.91		
			5	4943	3741	8.34		
			6	4648	4057	8.71		
			7	4305	4375	8.99		
6	C	2500	1	4373	1984	3.99	Y132S2-2	7.5
			2	4249	2333	4.45		
			3	4227	2679	4.95		
			4	3892	2952	5.07		
			5	3673	3225	5.34		
			6	3454	3497	5.58		
			7	3199	3772	5.76		

Shuangcheng Blower

Model 6-23

No.	Type	r/min	No.	Total pressure Pa	Flux m ³ /h	Power kW	motor	
							Type	Power kW
6	C	2400	1	4080	1917	3.61	Y132S-2	5.5
			2	3972	2255	4.02		
			3	3952	2590	4.47		
			4	3638	2853	4.58		
			5	3432	3117	4.83		
			6	3226	3381	5.05		
			7	2991	3646	5.21		
6	C	2000	1	2834	1598	2.09	Y100L-2	3
			2	2756	1879	2.32		
			3	2736	2158	2.59		
			4	2520	2378	2.65		
			5	2383	2598	2.79		
			6	2236	2817	2.92		
			7	2079	3038	3.01		
7	A	2930	1	8012	3655	13.47	Y160M ₂ -2	15
			2	7786	4297	15.01		
			3	7738	4936	16.69	Y160L-2	18.5
			4	7129	5438	17.09		
			5	6727	5941	18.03		
			6	6325	6443	18.84		
			7	5864	6948	19.42		
7	C	2500	1	6032	3173	8.82	Y160M ₂ -2	15
			2	5863	3730	9.82		
			3	5831	4284	10.92		
			4	5373	4721	11.18		
			5	5065	5157	11.80		
			6	4767	5592	12.32		
			7	4416	6031	12.70		
7	C	2400	1	5560	3046	7.80	Y160M1-2	11
			2	5404	3581	8.69		
			3	5374	4113	9.66		
			4	4952	4532	9.89		
			5	4668	4951	10.44		
			6	4393	5369	10.90		
			7	4070	5790	11.24		

Shuangcheng Blower

Model 6-23

No.	Type	r/min	No.	Total pressure Pa	Flux m ³ /h	Power kW	motor	
							Type	Power kW
7	C	2000	1	3864	2558	4.51	Y132S2-2	7.5
			2	3756	2984	5.03		
			3	3727	3428	5.59		
			4	3442	3776	5.72		
			5	3246	4126	6.04		
			6	3050	4474	6.29		
			7	2824	4825	6.51		
8	C	2880	1	10474	5456	23.64	Y200L1-2	30
			2	10170	6414	25.88		
			3	10120	7359	28.78		
			4	9316	8118	29.47		
			5	8787	8868	31.10	Y200L2-2	37
			6	8257	9683	32.50		
			7	7659	10371	33.50		
8	C	2500	1	7893	4736	15.85	Y180M-2	22
			2	7657	5568	17.66		
			3	7622	6397	19.66		
			4	7024	7047	20.12		
			5	6625	7698	21.22		
			6	6228	8404	22.20		
			7	5774	9002	22.85		
8	C	1800	1	4276	3486	6.32	Y132M-4	7.5
			2	4148	4098	7.04		
			3	4129	4708	7.84		
			4	3805	5187	8.02	Y160M1-4	11
			5	3589	5666	8.46		
			6	3374	6186	8.85		
			7	3128	6626	9.11		
8	C	1500	1	2844	2842	3.44	Y112M-4	4
			2	2756	3341	3.82		
			3	2746	3838	4.25		
			4	2530	4228	4.34	Y132S-4	5.5
			5	2383	4619	4.50		
			6	2236	5043	4.79		
			7	2079	5402	4.95		